

SONORAN

ST TIRES

OFFERING & SPECIFICATIONS

- » Engineered in the U.S.A.
- » Dual compound construction for longer tread life and reduced rolling resistance, improved fuel economy
- » Specialized tread pattern
- » Provides improved towing stability in all weather conditions
- » Superior quality maintained through 100% in-line automated uniformity testing
- » 6 Year Warranty
- » 1 Year, Hassle-Free Replacement
- » Dexter Defender Roadside Assistance Package

Size	Load Range	Ply Rating	Load Capacity		Speed Rating	Tread Depth
			Single	Dual		
ST175/80R13	C	6	1360 lbs/50 psi	N/A	N (87 mph)	7/32"
ST175/80R13	D	8	1610 lbs/65 psi	N/A	N (87 mph)	7/32"
ST185/80R13	C	6	1480 lbs/50 psi	N/A	N (87 mph)	7/32"
ST205/75R14	C	6	1760 lbs/50 psi	N/A	N (87 mph)	7/32"
ST205/75R14	D	8	2040 lbs/65 psi	N/A	N (87 mph)	7/32"
ST215/75R14	D	8	2200 lbs/65 psi	N/A	N (87 mph)	7/32"
ST205/75R15	C	6	1820 lbs/50 psi	N/A	N (87 mph)	7/32"
ST205/75R15	D	8	2150 lbs/65 psi	N/A	N (87 mph)	7/32"
ST225/75R15	D	8	2540 lbs/65 psi	N/A	N (87 mph)	7/32"
ST225/75R15	E	10	2860 lbs/80 psi	N/A	N (87 mph)	7/32"
ST235/80R16	E	10	3520 lbs/80 psi	3080 lbs/80 psi	N (87 mph)	7/32"
ST235/80R16	G	14	4080 lbs/110 psi	3640 lbs/110 psi	M (81 mph)	9/32"

DEXTERGROUP.COM

© 2005-2025 Dexter Axle Company | LIT-311-00 | 2025.01

