

SONORAN

ST TIRES



OFFERING & SPECIFICATIONS

- » Engineered in the U.S.A.
- » Dual compound construction for longer tread life and reduced rolling resistance, improved fuel economy
- » Specialized tread pattern
- » Provides improved towing stability in all weather conditions
- » Superior quality maintained through 100% in-line automated uniformity testing
- » 6 Year Warranty
- » 1 Year, Hassle-Free Replacement
- » Dexter Defender Roadside Assistance Package

Size	Load Range	Ply Rating	Load Capacity		Speed Rating	Tread Depth	*Tire Construction	
			Single	Dual			Sidewall	Tread
ST205/75R14	D	8	2040 lbs/65 psi	N/A	M (81 mph)	7/32"	2P	2P+2S+1N
ST205/75R15	C	6	1820 lbs/50 psi	N/A	M (81 mph)	7/32"	2P	2P+2S+1N
ST225/75R15	D	8	2540 lbs/65 psi	N/A	M (81 mph)	7/32"	2P	2P+2S+1N
ST235/80R16	E	10	3520 lbs/80 psi	3080 lbs/80 psi	M (81 mph)	7/32"	2P	2P+2S+1N
ST235/80R16	G	14	4080 lbs/110 psi	3640 lbs/110 psi	M (81 mph)	9/32"	2P	2P+2S+1N

*Tire Construction Abbreviations: P = Polyester; S = Steel; N = Nylon

www.dexteraxle.com

© 2005-2023 Dexter Axle Company | LIT-311-00 | 2023.10

